

# SterilDisk Probe with thread



Temperature data logger from -20°C to 140°C (calibration from 25°C to 140°C), with external probe with length on demand (probes cannot be switched) with first 10 mm with M5 thread (threaded part is included in probe length) on a 5 mm base (base height is not counted for probe length), IP68, in AISI316 L stainless steel, for sterilisation, pasteurisation, cooking processes monitoring. Managed through SPD and TS Manager (compatible with FDA 21 CFR Part 11 regulation) software and the interfaces DiskInterface HS Mini, DiskInterface HS and Multibay. Ideal for core of the product monitoring. It can be used alone or in combination with other loggers of the same model or different models, also for pressure monitoring. With every SterilDisk **a battery kit for battery replacement is included** and a **counterbolt with o-ring** for surface fixing. **Battery is user replaceable** and the data logger is **provided with an Accredia (NIST equivalent) traceable certificate** on 6 points.

Other available versions:

- SterilDisk: with internal sensor, for surface monitoring
- SterilDisk Probe 10: with 4 mm di diameter and 10 mm length probe, for a faster response time
- SterilDisk Probe: with 3 mm di diameter and 20/50/100/150 mm length probe
- SterilDisk Flexible: with 30 cm flexible probe and 50 mm length rigid probe

There are also other models of high temperature data loggers, for pressure and humidity too.

## Main features

- Small size
- With different lengths rigid probe for penetration
- With threaded part for quick and easy fixing to surfaces using the included counterbolt (open packages) or with the threaded rivet of the fixing kit (close packages)
- Completely food grade and waterproof
- **All software calculate lethality value (F0, PU, A0 ecc.)**
- User replaceable battery (**software shows battery status**)
- Accredia (NIST equivalent) traceable calibration certificate included
- Available **extended calibration from - 20°C** (order extra calibration points; in case of wide calibration range the accuracy might be worse)

## Plus

- High accuracy and precision
- Quick response time
- Printed reports compliant with health regulations and ISO (data are not editable in the software)
- Can be fixed to food package and surfaces with the Mounting Base

## The system

The system is made up by:

- SterilDisk temperature data logger



## Applications



Sterilisation



Pasteurisation



Food & Beverages



Pharmaceutical



Healthcare



Medical



Laboratories



Validation

- DiskInterface HS Mini or DiskInterface HS or Universal Multibay
- SPD software or TS Manager software (compatible with the FDA 21 CFR Part 11 regulation)

## **Accessories**

- SPD
- TS Manager
- DiskInterface HS Mini
- DiskInterface HS
- Universal multibay
- Counterbolt M5 thread with o-ring
- Fixing base
- Locking bolt
- Fastening system
- Teflon protective tube
- Battery kit for SterilDisk, PasteurDisk Can, SterilDisk Can
- O-rings for SterilDisk

## Technical specifications

Dimensions	17,4 h X 36,5 Ø (mm)
Probe dimensions	Probe base dimensions 5 h X 14 Ø (mm) - Probe I on demand X 3 Ø (mm) with first 10 mm with M5 thread (min. 20 mm / max. 185 mm. For longer probes ask for quotation)
Weight	82 gr
Materials	Stainless steel AISI316L, PEEK
Temperature range	-20 °C ÷ +140 °C
Standard calibration points (temperature)	25/50/75/100/121/140°C
Extra calibration points (temperature)	Within the range -20 °C ÷ +140 °C
Temperature resolution	0,01 °C
Temperature accuracy	± 0,2 °C (within the calibration range)
Memory (n. of acquisitions)	20.224
Acquisition step	From 1 every second up, with 1 second steps
Protection degree	IP68
Battery life	+1.400.000 acquisitions at 1 second step continuously (calculated time @25°C. Battery life may be shorter if used in low temperatures)
Software&Mobile App	SPD, TS Manager
Accessories	DiskInterface HS Mini, DiskInterface HS, Universal Multibay