

# DiskInterface HS



DiskInterface HS (High Speed) is the connection bay used for downloading data and programming all models of high temperature data loggers, included the models for pressure (PressureDisk) and humidity (RHTemp). There are also the DiskInterface HS Mini (all models of SterilDisk, il PasteurDisk Can and lo SterilDisk Can, P-Micro, S-Micro) or Universal Multibay (all models). It allows the communication between the data loggers and its management programs, SPD, HumiPressureDisk, TS Manager. Devices that can be connected are:

- SterilDisk (all versions)
- PasteurDisk Can
- SterilDisk Can
- P-Micro (all versions)
- S-Micro (all versions)
- S-Disk J (all versions)
- S-MicroW (all versions)
- P- Radio (all versions)
- S-Radio (all versions)
- PressureDisk (all versions)
- RHTemp (all versions)
- L-Disk (all versions)



## Main features

- Easy to use
- Status LED
- Shows battery status on software when logger is connected

## Accessories

- SPD
- HumiPressureDisk
- TS Manager
- Tecno Calib

## Technical specifications

Communication	USB
Cable	Included
Data loggers supported	SterilDisk, P-Micro, S-Micro, S-Disk J, S-MicroW, L-Disk, S-Radio, PasteurDisk, P-Radio, PressureDisk (solo la temperatura)

