TempStick Probe



TempStick Probe is a miniaturized temperature recorder with cable and rigid metal probe of verious lengths, with a wide range of monitoring applications especially in the food, environment and pharmaceutical industry, for continuous monitoring in fridges and fridge cells according to ISO 9001 and 12830 standards, HACCP, FDA, BRC ecc. certification. Its reduced size and no need of external power supply make the TempStick system extremely versatile. The data logger can be supplied with calibration certificate with Accredia (Italian reference center, NIST equivalent) traceability.



The battery is User replaceable.

The rigid metal probe is made with stainless steel AISI 316L, food grade, and is available in different types:

- 3 cm length, 4 mm diameter, rounded tip for immersion (ordering code 03)
- 8 cm length, 4 mm diameter, rounded tip for immersion (ordering code 04)
- 3 cm length, 4 mm diameter, pointed tip for penetration (ordering code 05)
- 8 cm length, 4 mm diameter, pointed tip for penetration (ordering code 06)

Main features

- Mission programming and reading using a PC through the TecnoStick Interface or SRI and FLI portable interfaces
- Reduced size for easy use for every need
- Quick response time
- **Stand-by function**: start the logger and then, using the metallic clip, set it to a stand by status. In this way you can send many pre-programmed loggers to the sender of the products without providing him with the software and the interface. Before sending the goods he will just have to remove the clip to start the acquisitions

Plus

- High accuracy and precision
- Product's core temperature controlled directly
- Easy to use with SRI and FLI portable interfaces
- Compliant with HACCP and EN12830 regulations
- **MKT formula implemented**, for quick data analysis, also on SRI and FLI
- Provided with calibration certificate Accredia (NIST equivalent) traceable (on demand)
- Long life battery
- User replaceable battery

Applications

Food & Beverages

Environment

Cold Chain

Pharmaceutical

Healthcare

Laboratories

Medical

Warehouses

Logistic&Transport

Industrial

The system

The TempStick system is made up by:
- TempStick data logger
- TS Manager 3 software
- TecnoStick Interface

Accessories

- TecnoStick Interface
- TempStick metal clip
- TS Manager 3

Technical specifications

Dimensions	54 X 32 X 11 (mm)
Probe dimensions	Cable 300 l X 4 Ø (mm) or longer - Probe 30 or 80 l X 4 Ø (mm) pointed or rounded
Weight	14 g
Temperature range	-30 °C ÷ +60 °C
Sensor temperature range	-40 °C ÷ +80 °C
Standard calibration points (temperature)	-30/0/20/60°C
Extra calibration points (temperature)	Within the range -40 °C ÷ +80 °C
Temperature resolution	0,03 °C
Temperature accuracy	± 1 °C without certificate / ± 0,25 °C with Accredia traceable certificate (valid in the calibration range)
Memory (n. of acquisitions)	2.730
Acquisition step	From 1 every minute to 1 every 255 minutes
Battery type	3.0V CR2032 lithium, user replaceable (2017 IATA DGR: PI970 Section II, < 4 cells)
Battery life	Up to 3 millions acquisitions @25°C +/- 10°C
Protection degree	IP63
Software&Mobile App	TS Manager 3
Accessories	TecnoStick Interface

tecnosoft
WE DELIVER DATA
Tecnosoft srl
Via Galvani, 4, 20068, Peschiera Borromeo (MI), Italy
T: (+39) 02 2692 2888 - F: (+39) 02 2692 2875
email: info@tecnosoft.eu - web: www.tecnosoft.eu
UNI EN ISO 9001:2008 Certiquality/IQNet N. 17733