# MicroW XL Flexible



MicroW L Flexible is a temperature data logger from -40°C to 140°C (calibration from 25°C to 140°C) with 30 cm felxible probe and 50 mm or on demand length external probe (probes cannot be switched) on a 5 mm base (base height is not counted for probe length), managed with Windows software and USB interface (DiskInterface HS, Multibay). **Battery** is **user replaceable** and the data logger is **provided with a National Reference traceable cetificate** on 6 points.
Note: if used below -30°C, battery life will be highly reduced.



## Applications

- Validation
- Sterilisation
- Pharmaceutical
- Healthcare
- Medical
- Laboratories
- Food & Beverages
- Pasteurisation

## Main features

- With flexible cable to reach points that requires minimum encumbrance by the device
- Completely food grade and waterproof
- **All software calculate lethality value (F0, PU, A0 ecc.)**
- Low battery consumption for an extended battery life
- User replaceable battery (**software shows battery status**)
- Very easy to deploy in any type of package
- Reference traceable calibration certificate included
- Available **extended calibration from -40°C** (order extra calibration points)

## Plus

- Extremely high accuracy and precision: with an accuracy of ± 0,1°C these devices can be employed in any application involving pharmaceuticals, validation, laboratory and medical field
- High accuracy even outside the calibration range
- Fast response time thanks to the 3 mm diameter probe
- Easy to use even in small and narrow places thanks to the flexible probe
- Printed reports compliant with health regulations and ISO (data are not editable in the software)

## The system

The system is made up by:

- MicroW XL Flexible temperature data logger
- DiskInterface HS or Universal Multibay
- TS Manager 3 software (compatible with the FDA 21 CFR Part 11 regulation)

## Accessories

- TS Manager 3
- Tecno Calib
- DiskInterface HS
- Universal multibay
- Locking bolt
- Fastening system
- MicroW L/XL, S-Micro L/XL heat protection 1
- MicroW L/XL, S-Micro L/XL heat protection 2
- MicroW XL battery kit

## Technical specifications

| | |
|---|---|
| Dimensions | 64 h X 20 Ø (mm) |
| Probe dimensions | Probe base dimensions 3 h X 14 Ø (mm) - Flexible probe 300 l X 2 Ø (mm) - Probe 50/on demand l X 3 Ø (mm) (l on demand: min. 40 mm / max. 175 mm. For longer probes ask for quotation) |
| Weight | 69 g |
| Materials | Stainless steel AISI316L, PEEK, FKM (o-ring) |
| Temperature range | -40°C ÷ +140°C |
| Standard calibration points (temperature) | 25/50/75/100/121/140°C |
| Extra calibration points (temperature) | Within the range -40 °C ÷ +140 °C |
| Temperature resolution | 0,01 °C |
| Temperature accuracy | ± 0,1 °C (within the calibration range) |
| Memory (n. of acquisitions) | 20.224 |
| Acquisition step | From 1 every second up, with 1 second steps |
| Protection degree | IP68 |
| Battery life | +17.000.000 acquisitions at 1 second step continuously (calculated time @25°C. Battery life may be shorter if used in low temperatures) |
| Software&Mobile App | SPD, TS Manager |
| Accessories | DiskInterface HS, Multibay universale |


