

MicroWH XL



MicroWH XL is a temperature data logger from -40°C to 150°C (standard calibration from 25°C to 150°C) with 20 mm or on demand length external probe (probes cannot be switched) on a 3 mm base (base height is not counted for probe length), managed with Windows software and USB interface (DiskInterface HS, Multibay). **Battery is user replaceable** and the data logger is **provided with a Reference traceable certificate** on 6 points.

Note: if used below -30°C, battery life will be highly reduced.



Main features

- With different lengths rigid probe for penetration
- Completely food grade and waterproof
- **All software calculate lethality value (F0, PU, A0 ecc.)**
- Low battery consumption for an extended battery life
- User replaceable battery (**software shows battery status**)
- Very easy to deploy in any type of package
- Reference traceable calibration certificate included
- For calibration over 150°C the minimum probe length is 50 mm

Plus

- Extremely high accuracy and precision: with an accuracy of $\pm 0,1^{\circ}\text{C}$ these devices can be employed in any application involving pharmaceuticals, validation, laboratory and medical field
- High accuracy even outside the calibration range
- Fast response time thanks to the 3 mm diameter probe
- Printed reports compliant with health regulations and ISO (data are not editable in the software)

The system

The system is made up by:

- MicroWH XL temperature data logger
- DiskInterface HS or Universal Multibay
- SPD software or TS Manager software (compatible with the FDA 21 CFR Part 11 regulation)

Accessories

- SPD
- TS Manager
- Tecno Calib
- DiskInterface HS
- Universal multibay
- Locking bolt
- Fastening system
- MicroW XL battery kit

Applications



Validation



Sterilisation



Pharmaceutical



Healthcare



Medical



Cosmetics



Laboratories



Food & Beverages



Pasteurisation

Technical specifications

| | |
|---|--|
| Dimensions | 64 h X 20 Ø (mm) |
| Probe dimensions | Probe base dimensions 3 h X 14 Ø (mm) - Probe 20/on demand I X 3 Ø (mm) (I on demand: min. 12 mm / max. 175 mm. For longer probes ask for quotation) |
| Weight | 61 g |
| Materials | Stainless steel AISI316L, PEEK |
| Temperature range | -40°C ÷ +150°C |
| Sensor temperature range | -40 °C ÷ +250 °C |
| Standard calibration points (temperature) | 25/50/75/100/121/150°C |
| Extra calibration points (temperature) | Within the range -40 °C ÷ +150 °C |
| Temperature resolution | 0,01 °C |
| Temperature accuracy | ± 0,1 °C (within the calibration range) / ± 0,05 °C with ultra accuracy option |
| Memory (n. of acquisitions) | 20.224 |
| Acquisition step | From 1 every second up, with 1 second steps |
| Protection degree | IP68 |
| Battery life | +17.000.000 acquisitions at 1 second step continuously (calculated time @25°C. Battery life may be shorter if used in low temperatures) |
| Software&Mobile App | SPD, TS Manager |
| Accessories | DiskInterface HS, Multibay universale |