# PressureDisk 05

PressureDisk 05 is a pressure data logger from 0 to 5 bar, managed with Windows software and USB interface (DiskInterface HS, Multibay). **Battery** is **user replaceable** and the data logger is **provided with an Accredia (NIST equivalent) traceable cetificate** on different points.

The other version of the data logger are:

 PressureDisk: pressure and temperature data logger from -40 to a140°C and from 0 to 5 bar

There are also other models of high temperature data loggers, for temperature only and humidity too.



# **Applications**



Validation



Sterilisation



Pharmaceutical



Medical



Healthcare



Laboratories



### **Main features**

- Resists up to 140°C
- Completely food grade and waterproof
- 1/4 Gas threaded connector to be screwed outside autoclave (the logger can still be used inside the autoclave though)
- TS Manager software calculates lethality value (F0, PU, A0 ecc.)
- Low battery consumption for an extended battery life
- User replaceable battery (software shows battery status)
- Accredia (NIST equivalent) traceable calibration certificate included
- Available extended calibration from -40°C (order extra calibration points)

### **Plus**

- Extremely high accuracy and precision: these devices can be employed in any application involving pharmaceuticals, validation, laboratory and medical field
- Printed reports compliant with health regulations and ISO (data are not editable in the software)

## The system

The system is made up by:

- PressureDisk temperature data logger
- DiskInterface HS or Universal Multibay
- TS Manager software (compatible with the FDA 21 CFR Part 11, Annex 11, GAMP 5 regulations)

### **Accessories**

- TS Manager 3
- PressureDisk, S-Disk J, L-Disk battery kit
- Filter for PressureDisk

# **Technical specifications**

Dimensions	43,22 h X 35 Ø (mm) - 55 (mm) total h with 1/4 Gas threaded part
Weight	145 g
Materials	Stainless steel AISI316L, PEEK, FKM (o-ring)
Pressure range	0 bar ÷ 5 bar absolute
Standard calibration points (pressure)	50/1k/2k/3k/4k absolute mbar
Extra calibration points (pressure)	Within the range 50 mbar ÷ 5 bar absolute
Pressure resolution	1 mbar
Pressure accuracy	± 15 mbar
Memory (n. of acquisitions)	27.264
Acquisition step	From 1 every second up
Protection degree	IP68
Battery life	+6.000.000 acquisitions at 1 second step continuously (calculated time @25°C. Battery life may be shorter if used in low temperatures)
Software&Mobile App	TS Manager 3, Tecno Calib
Accessories	DiskInterface HS, Multibay universale

