# RHTemp80 L

RHTemp80 L is a temperature and humidity data logger from -40°C to 80°C managed with Windows software and USB interface (DiskInterface HS, Multibay). **Battery** is **user replaceable** and the data logger is **provided with an Accredia (NIST equivalent) traceable cetificate** on different points.

It is available the model for up to 125°C.

Among the possible applications there are the drying processes monitoring, especially of pasta, of powders and grains storehouses, of extreme environments.



# **Applications**



Food & Beverages



Environment



Validation



Pharmaceutical



Healthcare



Cosmetics



Laboratories



Medica



Warehouses



Industrial

#### **Main features**

- Small size
- Completely food grade
- User replaceable battery (software shows battery status)
- Accredia (NIST equivalent) traceable calibration certificate included
- Available extended calibration from 40°C (order extra calibration points)

#### **Plus**

- High accuracy and precision
- Printed reports compliant with health regulations and ISO (data are not editable in the software)

## The system

The system is made up by:

- RHTemp temperature data logger
- DiskInterface HS or Universal Multibay
- HumiPressureDisk software or TS Manager software (compatible with the FDA 21 CFR Part 11 regulation)

### **Accessories**

- TS Manager
- HumiPressureDisk
- DiskInterface HS
- Universal multibay
- Battery kit for RHTemp80 L and RHTemp125 L

# **Technical specifications**

Dimensions	46 h X 17 Ø mm - 18 Ø (mm) PEEK ring
Weight	36 g
Materials	Stainless steel AISI316L, PEEK, FKM (o-ring)
Temperature range	-40°C ÷ +80°C
Standard calibration points (temperature)	23/50°C
Extra calibration points (temperature)	Within the range -40 °C ÷ +80 °C
Temperature resolution	0,015 °C
Temperature accuracy	$\pm$ 0,2 °C (0 °C $\div$ +60 °C) / $\pm$ 1,3 °C (-40 °C $\div$ +80 °C) / $\pm$ 2,3 °C (-40 °C $\div$ -20 °C) derates linearly
Humidity range	0% ÷ 100% RH (not condensing)
Standard calibration points (humidity)	30/50/70% @32°C ± 10°C
Extra calibration points (humidity)	Within the range 10% ÷ 90% RH
Humidity reslution	0,02%
Humidity accuracy	± 1,8% RH (10% ÷ 80%) / ± 4% RH (80% ÷ 90%) @ 23°C ± 10°C
Humidity drift	1% ÷ 2% / year (depends on use conditions)
Memory (n. of acquisitions)	10.112
Battery life	+8.000.000 acquisitions at 1 second step continuously (calculated time @25°C. Battery life may be shorter if used in low temperatures)
Acquisition step	From 1 every second up
Protection degree	IP50
Software&Mobile App	TS Manager 3, HumiPressureDisk, TS Manager
Accessories	DiskInterface HS, Multibay universale