MicroW L/XL, S-Micro L/XL heat protection 1

Heat protection for S-Micro L/XL / MicroW L/XL loggers, protects up to 250°C for a maximum of 17 minutes. This heat protection can be used in combination with S-Micro L/XL / MicroW L/XL heat protection 2.

It is possible to ask for extra calibration points up to 220°C, max calibrable and readable temperature, for the S-Micro L/XL data loggers, and up to 250 for MicroW L/XL (the probe only can reach such temperature, the data logger maximum operative temperature will always be 140°C).



Applications

Food & Beverages

Pharmaceutical

Industrial

Main features

- For calibration over 140°C the minimum probe length is 150 mm

Accessories

- MicroW L/XL, S-Micro L/XL heat protection 2

Technical specifications

Dimensions	190 h X 37 Ø (mm)
Weight	417 g
Data loggers supported	S-Micro L/XL, MicroW L/XL
Minimum probe length	50 mm
Materials	PTFE

tecnosoft
WE DELIVER DATA

Tecnosoft srl
Via Galvani, 4, 20068, Peschiera Borromeo (MI), Italy
T: (+39) 02 2692 2888 - F: (+39) 02 2692 2875
email: info@tecnosoft.eu - web: www.tecnosoft.eu
UNI EN ISO 9001:2008 Certiquality/IQNet N. 17733