

S-MicroW L Bendable 500



Temperature recording device from -40°C to 500°C (calibration from 25°C to 500°C, above 140°C the probe only resists) with 30 cm bendable probe and 2 mm diameter, managed with Windows software and USB interface (DiskInterface HS, Multibay). **Battery is user replaceable** and the data logger is **provided with an Accredia (NIST equivalent) traceable certificate** on 6 points.

Note: if used below -30°C, battery life will be highly reduced.



Main features

- With bendable cable to place the device near the packages instead on top and with rigid probe for penetration (first and last 15 mm cannot be bent)
- Completely food grade and waterproof
- **All software calculate lethality value (F0, PU, A0 ecc.)**
- Low battery consumption for an extended battery life
- User replaceable battery (**software shows battery status**)
- Very easy to deploy in any type of package
- Accredia (NIST equivalent) traceable calibration certificate included
- Available **extended calibration from -40°C to 500°C** (order extra calibration points; in case of wide calibration range the accuracy might be worse. Request the possible calibration ranges in advance)

Plus

- Extremely high accuracy and precision: with an accuracy of $\pm 0,1^{\circ}\text{C}$ these devices can be employed in any application involving pharmaceuticals, validation, laboratory and medical field
- Ultra Accuracy available ($\pm 0,05^{\circ}\text{C}$)
- High accuracy even outside the calibration range
- Fast response time thanks to the 3 mm diameter probe
- Easy to use even in small and narrow places thanks to the bendable probe
- Printed reports compliant with health regulations and ISO (data are not editable in the software)

The system

The system is made up by:

- S-MicroW L temperature data logger
- DiskInterface HS or Universal Multibay
- SPD software or TS Manager software (compatible with the FDA 21 CFR Part 11 regulation)

Applications



Validation



Sterilisation



Pharmaceutical



Healthcare



Medical



Cosmetics



Laboratories



Food & Beverages



Pasteurisation

Accessories

- SPD
- TS Manager
- Tecno Calib
- DiskInterface HS
- Universal multibay
- Locking bolt
- Fastening system
- Teflon protective tube
- S-MicroW L battery kit

Technical specifications

Dimensions	39 h X 20 Ø (mm)
Probe dimensions	Probe base dimensions 3 h X 14 Ø (mm) - Bendable probe 300/on demand 1 X 2 Ø (mm) (first and last 15 mm cannot be bent)
Weight	50 g
Materials	Stainless steel AISI316L, PEEK
Temperature range	-40°C ÷ +140°C
Sensor temperature range	-40 °C ÷ +500 °C
Standard calibration points (temperature)	25/50/75/100/121/140/200/250/300/400/500°C
Extra calibration points (temperature)	Nel range -40 °C ÷ +500 °C
Temperature resolution	0,01 °C
Temperature accuracy	± 0,1 °C (within the calibration range)
Memory (n. of acquisitions)	20.224
Acquisition step	From 1 every second up, with 1 second steps
Protection degree	IP68
Battery life	+10.000.000 acquisitions at 1 second step continuously (calculated time @25°C. Battery life may be shorter if used in low temperatures)
Software&Mobile App	SPD, TS Manager
Accessories	DiskInterface HS, Multibay universale