

TempNFC Calib



Reprogrammable version, with calibration certificate included, of the contact less temperature data logger with NFC technology managed through Android devices with dedicated App from Google Play. Allows to manage temperature monitoring using a Smartphone or a Tablet to INSTANTLY share the readings you downloaded. Developed especially but not only for transports and cold chain monitoring.

TempNFC Calib is reprogrammable data logger till calibration expiration date, reactivable with the recalibration: in this way you will be sure to use certified instruments.

Provided with a calibration certificate on the 4 standard points: -30/0/20/50°C.

Manage your loggers, share the information and focus only on your tasks.



Main features

- Start and download using NFC Android devices (download App from Google Play)
- Long life battery: 10 years or 3 millions of acquisitions
- Manual start option Mission status LED and button (running, stopped, OK, alarm)
- Check against alarm thresholds and transport duration
- MKT calculation is done on the App
- Bar Code and QR Code scan of the items being monitored in the shipment
- Geolocalization of the start and stop positions, saved with the mission data
- View readings in graphical or tabular format
- Create mission templates to quickly start the devices, without entering settings every time
- Additional Information: sender, receiver, operator, notes etc.
- Automatically send PDF reports to the email address set by the sender
- Synchronization with the Tecnosoft Cloud ([TempNFC Ent App](#))
- Accredia (NIST equivalent) traceable calibration certificate on one or more calibration points included

Plus

- Calibration included
- Certainty to use a calibrated device
- No extra accessory: your smartphone is all you need
- Small size suitable for every package and box
- Keep tracking of transported products along with temperature thanks to the bar code and QR codes

The system

TempNFC data logger does not need of any additional accessory. Just download the Android App and you are ready to start using it.

Accessories

- TempNFC Lite

Applications



Cold Chain



Logistic&Transport



Warehouses



Environment



Pharmaceutical



Medical



Healthcare



Cosmetics



Food & Beverages



Constructions



Industrial



Laboratories

- TempNFC Pro
- TempNFC Ent

Technical specifications

Dimensions	64 X 15 X 90 (mm)
Weight	18 g
Temperature range	-30 °C ÷ +50 °C
Standard calibration points (temperature)	1 point chosen among -30/0/20/50°C or 4 points
Extra calibration points (temperature)	Within standard calibration range
Temperature resolution	0,01 °C
Temperature accuracy	± 0.5 °C without certificate / ± 0,2 °C with Accredia traceable certificate (valid in the calibration range)
Memory (n. of acquisitions)	3.928 (may diminish according to the amount of notes)
Acquisition step	From 1 every second up, with 1 second steps
Buttons and functions	Start, status, limits check
Functions	LED for status: acquisition, stand by, out of limits
Battery type	3.0V CR2032 lithium (2017 IATA DGR: PI970 Section II, < 4 cells)
Battery life	Up to 10 years or 3 millions of acquisitions
Protection degree	IP65
Software&Mobile App	TempNFC Lite, TempNFC Pro, TempNFC Ent
It requires	NFC Android device